

COMPACT & EASY EVINRUDE PORTABLE ENGINES



HAVE A PASSION FOR WATER,
POWER, FISHING AND FUN?

E-NATION

JOIN THE CONVERSATION AT
EVINRUDE.COM/ENATION



COMPACT. Many features offered in a small package.

EASY. It's all about getting on the water and doing what you want to do.

EVINRUDE



PORTABLES 3.5 - 15 HP / 2.5 - 11 kW

GREAT THINGS COME IN SMALL PACKAGES.

EVINRUDE ENGINE SPECIFICATIONS

15 HP / 11 kW



9.8 HP / 7.2 kW



6 HP / 4.4 kW



4 HP / 2.9 kW



3.5 HP / 2.5 kW



ENGINE TYPE/TECHNOLOGY	2-cylinder/4-stroke	2-cylinder/4-stroke	1-cylinder/4-stroke	1-cylinder/4-stroke	1-cylinder/4-stroke
DISPLACEMENT	351 cc (21.41 cu.in.)	209cc (12.8 cu.in.)	123cc (7.5 cu.in.)	123cc (7.5 cu.in.)	86cc (5.2 cu.in.)
BORE X STROKE	61 x 60 mm (2.4 x 2.36 in)	55 x 44 mm (2.17 x 1.73 in)	59 x 45 mm (2.32 x 1.77 in)	59 x 45 mm (2.32 x 1.77 in)	55 x 36 mm (2.17 x 1.42 in)
STARTING	Electric or Manual	Electric or Manual	Manual	Manual	Manual
STEERING	Remote Control or Tiller Handle	Remote Control or Tiller Handle	Tiller Handle	Tiller Handle	Tiller Handle
GEAR SHIFT	Forward - Neutral - Reverse	Forward - Neutral - Reverse	Forward - Neutral - Reverse	Forward - Neutral - Reverse	Forward - Neutral
GEAR RATIO	2.15:1	2.08:1	2.15:1	2.15:1	2.15:1
PROPELLER SELECTION RANGE	6" - 10"	6.5" - 9.5"	6" - 9"	6" - 9"	4.5" - 7"
TRANSOM HEIGHT	38.1 cm, 50.8 cm (15", 20")	38.1 cm, 50.8 cm, 63.5 cm (15", 20", 25")	38.1 cm, 50.8 cm, 63.5 cm (15", 20", 25")	38.1 cm, 50.8 cm (15", 20")	38.1 cm, 50.8 cm (15", 20")
FUEL	Unleaded Gasoline (91 Octane)	Unleaded Gasoline (91 Octane)	Unleaded Gasoline (91 Octane)	Unleaded Gasoline (91 Octane)	Unleaded Gasoline (91 Octane)
OIL TYPE	NMMA Certified FC-W® 4-stroke oil SAE 10W-30/40 (SF, SG, SH, SJ)	NMMA Certified FC-W® 4-stroke oil SAE 10W-30/40 (SF, SG, SH, SJ)	NMMA Certified FC-W® 4-stroke oil SAE 10W-30/40 (SF, SG, SH, SJ)	NMMA Certified FC-W® 4-stroke oil SAE 10W-30/40 (SF, SG, SH, SJ)	NMMA Certified FC-W® 4-stroke oil SAE 10W-30/40 (SF, SG, SH, SJ)
OIL CAPACITY	1 qt. (1000 mL)	27 fl. oz. (800 mL)	15 fl. oz. (450 mL)	15 fl. oz. (450 mL)	10 fl. oz. (300 mL)
FUEL TANK	12 L Separate Fuel Tank	12 L Separate Fuel Tank	Internal Fuel Tank Models: 1.1 L Integral Tank	1.1 L Integral Tank	1 L Integral Tank
WEIGHT*	114.4 lbs. (52 kg)	81.5 lbs. (37 kg)	55 lbs. (25 kg)	57 lbs. (26 kg)	41 lbs (18 kg)
ALTERNATOR OUTPUT	Opt. Accessory: 12V, 145W, 12A (Standard on Electric Start Models)	Opt. Accessory: 12V, 80W, 6A (Standard on Electric Start Models)	Opt. Accessory: 12V, 60W, 5A (Standard on 25" shaft model)	Opt. Accessory: 12V, 60W, 5A	N/A
MAX. RPM RANGE	5,000 - 6,000	5,000 - 6,000	5,000 - 6,000	4,500 - 5,500	5,000 - 6,000
DIGITAL CD IGNITION SYSTEM	S	S	S	S	S
START IN GEAR PROTECTION	S	S	S	S	N/A
THERMOSTAT CONTROLLED COOLING SYSTEM	S	S	S	S	S
THROUGH-THE-PROP EXHAUST	S	S	S	S	N/A
SHALLOW WATER DRIVE	S	S	S	S	N/A
OIL PRESSURE WARNING	S	S	S	S	N/A
POWER TILT	O	O	N/A	N/A	N/A

* Weight based on lightest model.

©2012 Bombardier Recreational Products Inc. All rights reserved.

®, TM and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates.

EVINRUDE®



SEE MORE AT EVINRUDE.COM